

Алмазные коронки PRO



Модель	ID	Диаметр, мм	Длина, мм	Рабочая длина, мм	Количество сегментов	Размер сегмента, ДхШхВ, мм	Резьба	Тип бурения	Совместимость
102x350 Pro	52147	102	350	300	9	24x4x8	M22	Мокрый	    
102x450 Pro	52153	102	450	400	9	24x4x8	M22	Мокрый	    
108x350 Pro	52148	108	350	300	9	24x4x8	M22	Мокрый	    
108x450 Pro	52154	108	450	400	9	24x4x8	M22	Мокрый	    
112x350 Pro	52149	112	350	300	9	24x4x8	M22	Мокрый	   
112x450 Pro	52155	112	450	400	9	24x4x8	M22	Мокрый	   
120x350 Pro	52150	120	350	300	10	24x4x8	M22	Мокрый	   
120x450 Pro	52156	120	450	400	10	24x4x8	M22	Мокрый	   
132x350 Pro	52151	132	350	300	11	24x4x8	M22	Мокрый	   
132x450 Pro	52157	132	450	400	11	24x4x8	M22	Мокрый	   
152x350 Pro	52152	152	350	300	12	24x4.5x8	M22	Мокрый	   
152x450 Pro	52158	152	450	400	12	24x4.5x8	M22	Мокрый	   

 DD 2016  DD 4025  DD 4025 MF  DD 4030  DD 5035

**Данные параметры указаны для бетона. Для других материалов значения могут отличаться.*

Кроме того, для диаметров свыше 100 мм рекомендуется использование станины.